



Behnke Hydraulic Beavertail Flatbed



Behnke Hydraulic Beavertail Flatbed Specifications

Frame:

- 22lb i-beam frame and gooseneck
- (2) Dual speed jacks

Hitch:

- 2 5/16" Adjustable gooseneck coupler
- 3/8" Safety chains

Axles:

- 20,000lb GVW (24,000lb and 30,000lb available)
- (2) 10,000lb general duty oil bath axles with electric and forward self-adjusting brakes
- 10,000lb, 12,000lb, and 15,000lb heavy-duty axles available

Wheels & Tires:

- ST235/80R16E radial tires (dual wheel)
- Single and dual wheel options available
- Spare wheel & tire optional

Deck:

- 20', 22', 24', and 26' bed lengths available
- 8' 6" wide deck
- 2" X 8" treated wood floor
- Rub rail and stake pockets
- 12 X 12X 36" toolbox between uprights
- (2) 12 X 12 X 48" toolboxes underbody (power unit occupies 1 underbody toolbox)

Ankeny (Des Moines) • Council Bluffs (Omaha) • Lincoln • Norfolk • Sioux City



MIDWEST PETERBILT GROUP



- 10' beavertail (8' wood, 2' diamond plate)
- (2) 4" bore cylinders

Lights/Electrical:

- Rubber mounted sealed LED lights
- Light plug holder
- Reflector Tape
- Mud Flaps
- 12-Volt breakaway kit
- Modular wiring harness
- 12-V hydraulic pump
- Deep cell battery with charger

Finish:

- Zinc rich primed
- Powder Coated
- Standard colors: black, red, blue, gray, and yellowstone