



MIDWEST PETERBILT GROUP



Behnke Low Profile Dump Trailer



Behnke Low Profile Dump Trailer Specifications

Frame:

- 10,000lb jack

Hitch:

- 2 5/16" adjustable coupler or pintle hitch
- 3/8" safety chains
- 1/2" (grade 80) safety chains (20k GVW)

Axles:

- 12k-20k GVW available
- (2) 6k, 7k, 8k, or 10k axles available
- Electric and forward self-adjusting brakes

Wheels & Tires:

- Multiple size tires available

Ankeny (Des Moines) • Council Bluffs (Omaha) • Lincoln • Norfolk • Sioux City

**Box:**

- Available in 12', 14', 16', and 18' lengths
- 13-ton capacity Champion scissor hoist (12' box)
- 11-ton capacity Champion scissor hoist (14' and 16' boxes)
- 10.5-ton capacity Champion scissor hoist (18' box)
- 10-gauge solid steel sides (2' or 3' tall)
- 10-gauge steel floor (12k GVW)
- 3/16" steel floor (14k, 16k, and 20k GVW)
- 10-gauge solid steel combination gate (top swing, bottom swing, center split, and removable)
- 83" width between fenders
- Stake pockets
- 1.5" X ¼" flat tarp tie down
- 6' slide-in ramps
- (6) 5/8" d-rings (welded on sides, inside box)

Lights:

- Rubber mounted sealed LED lights
- Reflector Tape
- Modular wire harness

Finish:

- Zinc rich primed
- Powder Coated
- Standard colors: black, red, blue, gray, and yellowstone

Optional Items:

- Pallet fork holder
- Wireless remote
- 3/16" steel floor (12k GVW)
- ¼" steel floor (20k GVW)
- Dual batteries
- Roll tarp
- Spare tire mount
- 3rd axle (16' box or 20k GVW)
- 5-amp trickle charger
- Drop legs
- Gooseneck
- Solar charger