



MIDWEST PETERBILT GROUP



Behnke Structural Channel Equipment Trailer



Behnke Structural Channel Equipment Trailer Specifications

Frame:

- 10" structural channel
- 8" tall 3/16" sheet front rail
- 20,000lb dualpin dropleg jack

Hitch:

- 2 5/16" adjustable coupler or pintle hitch
- Safety chains

Axles:

- 14k-24k GVW available
- E-Z lube or oil bath axles standard
- Electric and forward self-adjusting brakes (both axles)

Wheels & Tires:

- Multiple size tires available
- 8-hole steel wheels

Deck:

- Available in 16', 18', 20', 22', and 24' lengths
- 1/8" heavy-duty formed fenders
- Stake pockets
- (8) d-rings

Ankeny (Des Moines) • Council Bluffs (Omaha) • Lincoln • Norfolk • Sioux City



MIDWEST PETERBILT GROUP



- Pallet fork holders
- 5' spring assist flip-up ramps
- 2" X 8" flush mounted treated wood
- Steel diamond plate beavertail

Lights:

- Rubber mounted sealed LED lights with plug holder
- Reflector Tape
- 12V breakaway kit
- Modular wire harness

Finish:

- Zinc rich primed
- Powder Coated
- Standard colors: black, red, blue, gray, and yellowstone

Optional Items:

- Rub rail
- Gooseneck hitch
- Bolt-on winch stand
- Oak or steel floor
- Toolbox
- Spare tire and wheel
- Bolt-on spare tire mount
- Fender guards