






XL Specialized 110 HDG Guardian



XL 110 HDG Guardian Specifications

Capacity:

- 110,000lb overall
- 110,000lb concentrated within 12'

Overall Length & Width:

- Overall length: 53'
- Overall width: 102"

Gooseneck:

- 13' low profile style neck with relief cutout
- 51" 5th wheel height
- 5 position variable ride height
- 110" & 84" swing clearance
- 16" & 42" king pin setting
- Hydraulics run off wet kit
- Air operated lock with manual safety latch
- Trilliant work light
- Toolbox in rear of neck with aluminum cover
- 13HP Honda power unit inside base of neck

Main Deck:

- 26' long
- T-1 flange, 80K web
- (4) 16" fabricated i-beams
- 22" loaded deck height
- 6" ground clearance
- 10" & 4" stubbed jr. i-beams on alternating 12" centers
- Top flange reinforcement
- 31" front flip ramps
- 7 bent d-rings per side
- 1 3/8" Apitong decking-raised open center
- Toolbox in front of deck
- 4 flat d-rings in toolbox
- Chain drops on 24" centers
- Heavy-duty swing out outriggers on 24" centers, double in center

Ankeny (Des Moines) • Council Bluffs (Omaha) • Lincoln • Norfolk • Sioux City







- Heavy-duty front pull out outrigger
- 1 pair EZ mount flag holders
- Bucket well at rear, plate on bottom
- 4 flat d-rings in bucket well

Rear Deck:

- 14' long with 32° rear transition
- 40" loaded deck height
- Open wheels-bolster style
- Open boom trough
- Air lift on 3rd axle
- 16.5" X 7" brakes
- Auto slack adjusters
- 54.5" axle spacing
- 1 pair flat d-rings on main beams at front
- 1 pair flat d-rings on main beams at rear
- 2 pair flat d-rings in boom trough
- 2 chain drops on each bolster
- 1 pair EZ mount flag holders
- 2 stake pockets in tail channel for wide load sign
- Frame reinforcement for 1-axle booster
- 4-way plug at rear

Suspension:

- 25,000lb air ride
- Raise and lower valve
- Manual ride height control
- Liquid filled air gauge

Axles:

- (3) 25,000lb nominal axles
- Spring brakes on 1 axle
- ABS not required

Wheels & Tires:

- 8.25" X 22.5" steel wheels (aluminum available)
- 255/70R22.5" tires
- Hub pilot, outboard drums

Lighting:

- 12V sealed Grote harness
- Rubber mounted LED lights
- 3 taillight package with aluminum cover
- 4" amber strobe as 3rd taillight
- 4 clearance lights per side (1 at rear, 1 at front, 2 on main deck)
- 1 mid-turn light per side
- 7 pole electric socket

Ankeny (Des Moines) • Council Bluffs (Omaha) • Lincoln • Norfolk • Sioux City







Paint:

- Black, IH red, CAT yellow, white available
- Air & electric done after paint

Warranty:

- 5-year structural warranty
- 3-year paint warranty
- 1-year parts and components warranty







